


COM & SEG LAYOUT



DOTS SIDE SCALE 20:1

PIN	SYMBOL
1	CS1B
2	/RES
3	A0
4	D6(SCLK)
5	D7(SDA)
6	VDD
7	VSS
8	V0
9	XV0
10	VG
11	A
12	K

备注：背光和HFG13232-02共用

NOTES :

- LCD TYPE: FSTN Positive Transflective
- OPERATING VOLTAGE: VDD=3.0V, Vop=6.2V
- VIEWING DIRECTION: 12 O'CLOCK
- DRIVE METHOD: 1/32 Duty, 1/6 Bias
- OPERATING TEMP: -20°C TO +70°C
- STORAGE TEMP: -30°C TO +80°C
- CONNECTOR TAPE: COG+FPC
- DRIVER IC: ST7567 or Equivalent
- BACKLIGHT: 2 Pcs White LEDs VF=3.1±0.1V, IF=15x2mA
- ALL sub-parts and materials of the parts, must comply with the RoHS instructions of EU.

SHEET: 1 of 1	
APPROVALS	DATE
DWN SD-02	2016-10-20
CHK	
APP SD-11	2016-10-20

**SINDA DISPLAY TECHNOLOGY CO., LTD.**

MODEL NUMBER :	VERSION: 1.0	UNITS: MM
SDGG13232-02	GENERAL TOL: ± 0.2	
DO NOT SCALE THIS DRAWING.		
www.sindadisplay.com		SCALE: 1:1