


REV:	DESCRIPTION	BY	DATE
V1.0	New issue	Mike	2018-03-21

NO	Symbol
1	NC
2	/CS1
3	/RES
4	A0
5	/WR
6	/RD
7	DB0
8	DB1
9	DB2
10	DB3
11	DB4
12	DB5
13	DB6
14	DB7
15	VSS
16	VDD
17	VOUT
18	CAP1N
19	CAP3P
20	CAP1N
21	CAP1P
22	CAP2P
23	CAP2N
24	VR
25	V4
26	V3
27	V2
28	V1
29	V0
30	VDD



- NOTES :
- | | |
|---|-------------------------------|
| 1. LCD TYPE: | STN-Gray, Positive Reflective |
| 2. OPERATING VOLTAGE: | VDD=3.0V, Vop=10.9V |
| 3. VIEWING DIRECTION: | 6 O'CLOCK |
| 4. DRIVE METHOD: | 1/65 Duty, 1/9 Bias |
| 5. OPERATING TEMP: | -20°C TO +70°C |
| 6. STORAGE TEMP: | -30°C TO +80°C |
| 7. CONNECTOR TAPE: | COG |
| 8. DRIVER IC: | ST7565P or Equivalent |
| 9. BACKLIGHT: | |
| 10. ALL sub-parts and materials of the parts, must comply with the RoHS instructions of EU. | |

SINDA DISPLAY TECHNOLOGY CO., LTD.	
SHEET: 1 of 1	
APPROVALS	DATE
DWN Mike	2018-03-21
CHK	
APP CJ	2018-03-21
MODEL NUMBER : SDGG12864-16	
VERSION: 1.0	UNITS: MM
GENERAL TOL: ± 0.2	
DO NOT SCALE THIS DRAWING.	
www.sindadisplay.com	
SCALE: 1:1	