



正反面贴黑胶带

PIN	Configuration	
1	BLK	
2	BLA	
3	SCK	⊖ P1.0
4	SDA	⊖ P1.1
5	/RES	⊖ P3.6
6	/CS0	⊖ P3.5
7	CD	⊖ P3.7
8	VSS	⊖ 0 V
9	VDD	⊖ +3.3V
10	VBO+	2.2uF
11	VB1+	
12	VB1-	2.2uF
13	VBO-	
14	VLCD	330nF 3.3Mohm VSS

REV:	DESCRIPTION	BY	DATE
V1.0	New issue	Mike	2014-07-14

- NOTES:
- |                           |                      |
|---------------------------|----------------------|
| 1. DISPLAY TYPE:          | FSTN/POSITIVE        |
| 2. OPERATING VOLTAGE:     | Vdd=3.0V, Vlcd=13.0V |
| 3. OPERATING TEMPERATURE: | 0°C~50°C             |
| 4. STORAGE TEMPERATURE:   | -10°C~60°C           |
| 5. DRIVE MODE:            | 1/128D, 1/12B        |
| 6. VIEWING DIRECTION:     | 6:00                 |
| 7. POLARIZER TYPE:        | TRANSMISSIVE         |
| 8. CONNECTOR:             | COG/UC1617s          |
| 9. CUSTOMER No.:          |                      |

		<b>SINDA DISPLAY TECHNOLOGY CO., LTD.</b>	
SHEET: 1 of 1		MODEL NUMBER : SDGG128128-06	VERSION: 1.0
APPROVALS	DATE	UNITS: MM	
DWN Mike	2014-07-14	GENERAL TOL: ± 0.2	
CHK		DO NOT SCALE THIS DRAWING.	
APP CJ	2014-07-14	SCALE: 1:1	
		www.sindadisplay.com	