


REV:	DESCRIPTION	BY	DATE
V00	New issue	SD-02	2019-04-01

NOTES:

1. ALL DIMENSIONS ARE mm.
2. LCD TYPE: STN-BLUE, NEGATIVE
3. POLARIZER MODE: TRANSMISSIVE
4. OPERATING VOLTAGE: VDD=5.0V, Vop=17.0V
5. VIEWING DIRECTION: 6.00 O'CLOCK
6. DRIVE METHOD: 1/128 DUTY, 1/12 BIAS
7. OPERATING TEMP: -20°C TO +70°C.
8. STORAGE TEMP: -30°C TO +80°C.
9. CONNECTOR TAPE: ZEBRA
10. DRIVER IC: T6963 or Equivalent
11. BACKLIGHT: WHITE,
12. ALL sub-parts and materials of the parts must comply with the RoHS instructions of EU.

J1引脚定义

PIN	1	2	3	4	5	6	7	8	9	10	11	12	13
NAME	FG	GND	VDD	VO	/WR	/RD	/CE	C/D	NC	RST	DB0	DB1	DB2
PIN	14	15	16	17	18	19	20	21	22	23	24	25	
NAME	DB3	DB4	DB5	DB6	DB7	FS1	VEE	LEDA	LEDK	LEDA	NC	LEDK	

 SINDA DISPLAY TECHNOLOGY CO., LTD.	
SHEET: 1 of 1	
APPROVALS DATE	
DWN SD-02 2019-04-01	
CHK SD-11 2019-04-01	
APP SD-11 2019-04-01	
MODEL NUMBER : SDGB240128-06	
SCALE: 1:1 UNITS: MM	
GENERAL TOL: ± 0.2	
DO NOT SCALE THIS DRAWING.	
www.sindadisplay.com VERSION: 1.0	